




Doorphone Features:

- New high quality metallic finish
- Call button surrounded by luminous ring



(in darkness)



*1 If the ring is not exposed to light, it will not emit light.

- Suitable for home and office use
- Wall Mountable



The T7765 is a new high quality design doorphone. It is suitable for home and small office use on any door type with its metallic finish.

The T7765 connects directly to Panasonic's PBX and allows callers to easily speak with your staff. At dusk, visitors can easily find the call button thanks to the luminous ring, making access so much quicker.



T7765 Specifications

Luminous Ring Specifications

- Once exposed to light (min 30 min), this ring keeps emitting light for about 1 hour in the darkness*
Max. residual lighting time: About 1.5 hours
- If exposed to any light, the ring emits light repeatedly.

Notes:

- The duration of light emission varies according to light exposure, accumulation and temperature, installation etc.

Capability & Hardware Requirements

The Panasonic KX-T7765 Doorphone is compatible with the following Panasonic PBX systems.

KX-TDE100/200	Optional doorphone, OPB card and DPH card
KX-TDA100/200/600	Optional doorphone, OPB card and DPH card
KX-TDA30	Optional doorphone and DPH card
KX-TE824 /TE308/TEB11	Optional doorphone and DPH card

Maximum Number of Doorphones

Model No.	TDA30	TDE100 TDA100	TDE200 TDA200	TDA600	TE824	TE308 TEB11
Number of doorphones	4	16	16	16/32/48/64	4	2

Maximum Cabling Distance

TDE/TDA Series		Cable	Maximum Distance	
		ø 0.4 mm :	70 m	
		ø 0.5 mm :	113 m	
		ø 0.6 mm :	180 m	
CAT 5 :		113 m		
TE824 Series		Cable	Maximum Distance	
		ø 0.4 mm :	70 m	
		ø 0.5 mm :	110 m	
		ø 0.65 mm :	150 m	
CAT 5 :		110 m		
TE308 Series		Cable	Maximum Distance	
		ø 0.4 mm :	70 m	
		ø 0.5 mm :	110 m	
		ø 0.65 mm :	150 m	
CAT 5 :		110 m		

Dimensions



Panasonic